


ROUND DEEP/SPOT DOWNLIGHT/FIXED

Model: RR-DL3241



➤ Cutout: 68mm

⚙️ 5-25mm

Feature:

- Deep recessed
- Compact design
- High quality PMMA lens in different beam angles

Technical data:

- Light source COB Chip, Cree or others
- LED Power (max) 9W (250mA, 36V)
- System Power (ref.) 11W (ref. only depends on the ECG)
- Lumen flux (typ.) 800lm @10W
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index Ra \geq 90
- MacAdam step 3
- Beam Angle 24D, 36D, 45D PMMA lens
- Tilttable No
- Ingress protection IP44
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White RAL9016/Black RAL9005
- Construction Aluminum, Polycarbonate
- Installation Ceiling Recessed, spring type
- Dimension 74mm(OD)x55mm(H)/Cutout 68mm
- LED Driver Remote
- Trimless version Yes, Please check with sale in detail

Electronic control gear

NON-DIM/Dimmable

IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.

LIGHT DISTRIBUTION for 3000K medium 36°

h(m)	E(lx)	Ø(m)
1	1218	Ø0.65
2	304.6	Ø1.30
3	135.4	Ø1.95
4	76.15	Ø2.60
5	48.74	Ø3.25

Photometric 3000K 36D Ra.90

****The specification is subject to change without note.****