

## DOUBLE REFLECT/SPOT LIGHT/ANTI-GLARE

**Model: RR-DL3292**



### Feature:

- Compact Design with deep recessed
- Small cutout
- Very Low UGR

### Technical data:

- |                          |                                   |
|--------------------------|-----------------------------------|
| ▪ Light source           | COB or others                     |
| ▪ LED Power (max)        | 5.4W (150mA, 36V)                 |
| ▪ System Power (ref.)    | 7W (ref. only depends on the ECG) |
| ▪ Lumen flux (typ.)      | 400lm                             |
| ▪ Colour temperature     | 2700K, 3000K, 4000K               |
| ▪ Colour rendering index | Ra $\geq$ 90                      |
| ▪ MacAdam Step           | 3                                 |
| ▪ Beam Angle             | 22D, 40D PMMA Lens                |
| ▪ Tilttable              | No                                |
| ▪ Ingress protection     | IP21                              |
| ▪ Operation temperature  | 0-40C                             |
| ▪ Protection Class       | III                               |
| ▪ LED Life time          | 50,000h L70B10                    |
| ▪ Finishing              | White/Black                       |
| ▪ Baffle Finishing       | Plain White/Plain Black/ Chrome   |
| ▪ Construction           | Aluminum                          |
| ▪ Installation           | Ceiling Recessed, spring type     |
| ▪ Dimension              | 34mm(OD)x94mm(H)/Cutout 28mm      |
| ▪ LED Driver             | Remote                            |
| ▪ Trimless version       | No                                |

### Electronic control gear

NON-DIM/Dimmable

**IDP** MP series

1-10V/0-10V/DALI

**IDP** SC series


Other brand is available upon request

\*Use IDP multi-power LED Driver can trim down the output power according to actual application.

### Light Distribution For 3000K

spot 16.5°			medium 33.2°		
h(m)	E(lx)	ø(m)	h(m)	E(lx)	ø(m)
1	2645	ø0.29	1	1985	ø0.35
2	661.2	ø0.58	2	496.3	ø0.70
3	293.9	ø0.87	3	220.6	ø1.06
4	185.3	ø1.16	4	124.1	ø1.41
5	105.8	ø1.45	5	79.41	ø1.77

**\*\*The specification is subject to change without note.\*\***



⊕ Cutout: 28mm

⊕ 5-25mm