

DOUBLE REFLECT/SPOT LIGHT/WALL WASHER

Model: RR-DL3291



Feature:

- Compact design with wall washer
- Small cutout
- Ver Low UGR

Technical data:

▪ Light source	COB or others
▪ LED Power (max)	5.4W (150mA, 36V)
▪ System Power (ref.)	7W (ref. only depends on the ECG)
▪ Lumen flux (typ.)	350lm
▪ Colour temperature	2700K, 3000K, 4000K
▪ Colour rendering index	Ra≥90
▪ MacAdam Step	3
▪ Beam Angle	56D PMMA Lens
▪ Tilttable	Yes
▪ Ingress protection	IP21
▪ Operation temperature	0-40C
▪ Protection Class	III
▪ LED Life time	50,000h L70B10
▪ Finishing	White/Black
▪ Baffle Finishing	Plain White/Plain Black/ Chrome
▪ Construction	Aluminum
▪ Installation	Ceiling Recessed, spring type
▪ Dimension	34mm(OD)x83mm(H)/Cutout 28mm
▪ LED Driver	Remote
▪ Trimless version	No

Electronic control gear

NON-DIM/Dimmable

IDP MP series

1-10V/0-10V/DALI


IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.

Light Distribution For 2700K wide 56°

h(m)	E(lx)	ø(m)
1	331.7	ø0.99
2	82.92	ø1.98
3	36.85	ø2.97
4	20.73	ø3.97
5	13.27	ø4.96



↻ Cutout: 28mm

≡ 5-25mm

****The specification is subject to change without note.****