



BLACK HOLE/SPOT LIGHT/FIXED

Model: RR-DL3357



↻ Cutout: 35mm
 5-25mm

Feature:

- MINI Size
- Black Ring
- Low UGR

Technical data:


▪ Light source	COB or others
▪ LED Power (max)	5.4W (150mA, 36V)
▪ System Power (ref.)	7W (ref. only depends on the ECG)
▪ Lumen flux (typ.)	500lm
▪ Colour temperature	2700K, 3000K, 4000K
▪ Colour rendering index	Ra≥90
▪ MacAdam Step	3
▪ Beam Angle	20D, 40D PMMA Lens
▪ Tilttable	No
▪ Ingress protection	IP21
▪ Operation temperature	0-40C
▪ Protection Class	III
▪ LED Life time	50,000h L70B10
▪ Finishing	White/Black
▪ Baffle Finishing	Black
▪ Construction	Aluminum
▪ Installation	Ceiling Recessed, Spring type
▪ Dimension	42mm(OD)x50mm(H)/Cutout 35mm
▪ LED Driver	Remote
▪ Trimless version	No

Electronic control gear

NON-DIM/Dimmable

 MP series

1-10V/0-10V/DALI

 SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.

Light Distribution For 3000K

medium 20°

wide 36°

h(m)	E(lx)	ø(m)	h(m)	E(lx)	ø(m)
1	1985	ø0.35	1	835.0	ø0.63
2	496.3	ø0.70	2	208.7	ø1.27
3	220.6	ø1.06	3	92.77	ø1.91
4	124.1	ø1.41	4	52.19	ø2.55
5	79.41	ø1.77	5	33.40	ø3.19

The specification is subject to change without note.