

BLACK HOLE/SPOT LIGHT/TILTABLE/SNOOT

Model: RR-DL3382



Feature:

- Compact size
- Compact snoot
- Low UGR

Technical data:

▪ Light source	COB or others
▪ LED Power (max)	9W (250mA, 36V)
▪ System Power (ref.)	11W <small>(ref. only depends on the ECG)</small>
▪ Lumen flux (typ.)	800lm
▪ Colour temperature	2700K, 3000K, 4000K
▪ Colour rendering index	Ra≥90
▪ MacAdam Step	3
▪ Beam Angle	15D, 24D, 36D, 50D PMMA Lens
▪ Tiltable	Yes
▪ Ingress protection	IP21
▪ Operation temperature	0-40C
▪ Protection Class	III
▪ LED Life time	50,000h L70B10
▪ Finishing	White/Black
▪ Baffle finishing	Black
▪ Construction	Aluminum
▪ Installation	Ceiling Recessed, Spring type
▪ Dimension	92mm(OD)x76mm(H)/Cutout 82mm
▪ LED Driver	Remote
▪ Trimless versin	Yes, please contact us in detail

Electronic control gear

NON-DIM/Dimmable

IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

****The specification is subject to change without note.****

