


SIMPLE/SPOT LIGHT/FIXED

Model: RR-DL3041



↻ Cutout: 83mm

⚙️ 5-25mm

Feature:

- Compact size
- Step in design
- IP54

Technical data:

- Light source COB or others
- LED Power (max) 9W (250mA, 36V)
- System Power (ref.) 11W (ref. only depends on the ECG)
- Lumen flux (typ.) 650lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index Ra \geq 90
- MacAdam Step 3
- Beam Angle 24D, 36D, 45D PMMA Lens
- Tilttable Yes
- Ingress protection IP54
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Construction Aluminum
- Installation Ceiling Recessed, Spring type
- Dimension 92mm(OD)x57mm(H)/Cutout 83mm
- LED Driver Remote
- Trimless version No

Electronic control gear

NON-DIM/Dimmable

IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.

Light Distribution For 3000K

medium 36°			wide 47°		
h(m)	E(lx)	ø(m)	h(m)	E(lx)	ø(m)
1	1218	ø0,65	1	1399	ø0,86
2	304.6	ø1,30	2	349.7	ø1,73
3	135.4	ø1,95	3	155.4	ø2,60
4	76.15	ø2,60	4	78.44	ø3,47
5	48.74	ø3,25	5	55.96	ø4,34

****The specification is subject to change without note.****