

SIMPLE/SPOT LIGHT/TWIN HEADS/FIXED

Model: SR-DL0043



Feature:

- Compact size
- Step in design
- Twin Head

Technical data:

- Light source COB or others
- LED Power (max) 9W x 2 (250mA x 2, 36V)
- System Power (ref.) 11W x 2 (ref. only depends on the ECG)
- Lumen flux (typ.) 1300lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index Ra ≥ 90
- MacAdam Step 3
- Beam Angle 24D, 36D, 45D PMMA Lens
- Tilttable No
- Ingress protection IP54
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Construction Aluminum
- Installation Ceiling Recessed, Spring type
- Dimension 170x91mm x 57mm(H)/Cutout 160x85mm
- LED Driver Remote
- Trimless version No

Electronic control gear

NON-DIM/Dimmable


IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.



▧ Cutout: 160x85mm

▧ 5-25mm

Light Distribution For 3000K

medium 20°

wide 36°

h(m)	E(lx)	ø(m)	h(m)	E(lx)	ø(m)
1	2906	ø0.63	1	1892	ø0.95
2	726.6	ø1.28	2	427.9	ø1.90
3	322.9	ø1.93	3	210.2	ø2.86
4	181.6	ø2.57	4	118.2	ø3.81
5	116.3	ø3.22	5	75.60	ø4.76

****The specification is subject to change without note.****