


SIMPLE/SPOT LIGHT/SQUARE/GIMBLE

Model: RR-DL3166



▤ Cutout: 90x90mm

▤ 5-25mm

Feature:

- Compact size with step in design
- Gimble tilt 25 degree
- Low UGR

Technical data:

- Light source COB or others
- LED Power (max) 7.2W (200mA, 36V)
- System Power (ref.) 9W (ref. only depends on the ECG)
- Lumen flux (typ.) 600lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index Ra \geq 90
- MacAdam Step 3
- Beam Angle 24D, 36D, 45D PMMA Lens
- Tiltable Yes
- Ingress protection IP21
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Construction Aluminum
- Installation Ceiling Recessed, Spring type
- Dimension 100x100mmx55mm(H)/Cutout 90x90mm
- LED Driver Remote
- Trimless version Yes, Please contact us in detail

Electronic control gear

NON-DIM/Dimmable

IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

Light Distribution For 3000K

medium 36°			wide 44°		
h(m)	E(lx)	ø(m)	h(m)	E(lx)	ø(m)
1	955.6	ø0.81	1	738.7	ø0.83
2	238.9	ø1.62	2	184.7	ø1.67
3	106.2	ø2.43	3	82.08	ø2.51
4	59.73	ø3.24	4	46.17	ø3.34
5	38.23	ø4.06	5	29.55	ø4.17

**Th