




SQUARE/SPOT LIGHT/MINI/BOX/SINGLE/TILTABLE

Model: SR-DL3444



 Cutout: 55x55mm

 5-25mm

Feature:

- Single head square grilled downlight
- Interchangeable baffle
- Compact design

Technical data:

- Light source COB or others
- LED Power (max) 5.4W (150mA, 36V)
- System Power (ref.) 7W (ref. only depends on the ECG)
- Lumen flux (typ.) 350lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index Ra \geq 90
- MacAdam Step 3
- Beam Angle 15D, 24D, 36D PMMA Lens
- Tilttable Yes
- Ingress protection IP21
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Baffle Finishing Plain White/Plain Black/Brushed Brass
- Construction Aluminum
- Installation Ceiling Recessed, spring type
- Dimension 64x64mmx65mm(H)/Cutout 55x55mm
- LED Driver Remote
- Trimless version No

Electronic control gear

NON-DIM/Dimmable

 MP series

1-10V/0-10V/DALI

 SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.

Light Distribution For 3000K

spot 24°

medium 36°

h(m)	E(lx)	ø(m)	h(m)	E(lx)	ø(m)
1	1021	ø0.18	1	587.2	ø0.25
2	255.4	ø0.36	2	146.84	ø0.51
3	113.52	ø0.54	3	65.28	ø0.76
4	63.84	ø0.72	4	36.72	ø1.02
5	40.88	ø0.91	5	23.48	ø1.27

****Accessories (optional): Honeycomb louvre**

****The specification is subject to change without note.****