

SQUARE/SPOT LIGHT/ MINI/BOX/TWIN HEADS/TILTABLE

Model: SR-DL3445



Feature:

- TWIN heads square grilled downlight
- Interchangeable baffle
- Compact design

Technical data:

| | |
|--------------------------|---------------------------------------|
| ▪ Light source | COB or others |
| ▪ LED Power (max) | 5.4W x 2 (150mA x 2 , 36V) |
| ▪ System Power (ref.) | 7W x 2 (ref. only depends on the ECG) |
| ▪ Lumen flux (typ.) | 350lm x 2 |
| ▪ Colour temperature | 2700K, 3000K, 4000K |
| ▪ Colour rendering index | Ra≥90 |
| ▪ MacAdam Step | 3 |
| ▪ Beam Angle | 15D, 24D, 36D PMMA Lens |
| ▪ Tilttable | Yes |
| ▪ Ingress protection | IP21 |
| ▪ Operation temperature | 0-40C |
| ▪ Protection Class | III |
| ▪ LED Life time | 50,000h L70B10 |
| ▪ Finishing | White/Black |
| ▪ Baffle Finishing | Plain White/Plain Black/Brushed Brass |
| ▪ Construction | Aluminum |
| ▪ Installation | Ceiling Recessed, spring type |
| ▪ Dimension | 103x64mmx65mm(H)/Cutout 94x55mm |
| ▪ LED Driver | Remote |
| ▪ Trimless version | No |

Electronic control gear

NON-DIM/Dimmable

IDP MP series

1-10V/0-10V/DALI


IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.

Light Distribution For 3000K

| spot 24° | | | medium 36° | | |
|----------|-------|-------|------------|-------|-------|
| h(m) | E(lx) | ø(m) | h(m) | E(lx) | ø(m) |
| 1 | 1532 | ø0.27 | 1 | 880.8 | ø0.38 |
| 2 | 383.1 | ø0.54 | 2 | 220.2 | ø0.76 |
| 3 | 170.2 | ø0.81 | 3 | 97.92 | ø1.14 |
| 4 | 95.76 | ø1.09 | 4 | 55.08 | ø1.53 |
| 5 | 61.32 | ø1.36 | 5 | 34.84 | ø1.91 |



Cutout: 94x55mm

5-25mm

****Accessories (optional): Honeycomb louvre**

****The specification is subject to change without notes.****