

## SQUARE/SPOT LIGHT/MINI/BOX/TRIPLE HEADS/TILTABLE

**Model: SR-DL3446**



### Feature:

- TRIPLE heads square grilled downlight
- Interchangeable baffle
- Compact design

### Technical data:

- Light source COB or others
- LED Power (max) 5.4W x 3 (150mA x 2 , 36V)
- System Power (ref.) 7W x 3 (ref. only depends on the ECG)
- Lumen flux (typ.) 350lm x 3
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index Ra $\geq$ 90
- MacAdam Step 3
- Beam Angle 15D, 24D, 36D PMMA Lens
- Tilttable Yes
- Ingress protection IP21
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Baffle Finishing Plain White/Plain Black/Brushed Brass
- Construction Aluminum
- Installation Ceiling Recessed, spring type
- Dimension 142x64mmx65mm(H)/Cutout 133x55mm
- LED Driver Remote
- Trimless version No


### Electronic control gear


NON-DIM/Dimmable **IDP** MP series


1-10V/0-10V/DALI **IDP** SC series

Other brand is available upon request

\*Use IDP multi-power LED Driver can trim down the output power according to actual application.



 Cutout: 133x55mm

 5-25mm

#### Light Distribution For 3000K

spot 24°			medium 36°		
h(m)	E(lx)	ø(m)	h(m)	E(lx)	ø(m)
1	2554	ø0.45	1	1468	ø0.64
2	638.6	ø0.91	2	367.1	ø1.27
3	283.8	ø1.36	3	163.2	ø1.91
4	159.6	ø1.82	4	91.80	ø2.55
5	102.2	ø2.27	5	58.70	ø3.19

**\*\*Accessories (optional): Honeycomb louvre**

**\*\*The specification is subject to change without notes.\*\***