


SQUARE/SPOT LIGHT/MEDIUM/BOX/TRIPLE HEADS/TILTABLE

Model: SR-DL3350



Cutout: 280x100mm

5-25mm

Feature:

- TRIPLE head square grilled downlight
- Gimble tilt 30 degree
- Compact design with IP54

Technical data:

- Light source COB or others
- LED Power (max) 9W x 3 (250mA x 2, 36V)
- System Power (ref.) 11W x 3 (ref. only depends on the ECG)
- Lumen flux (typ.) 1200lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index Ra \geq 90
- MacAdam Step 3
- Beam Angle 24D, 36D, 45D PMMA Lens
- Tilttable Yes
- Ingress protection IP54
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Construction Aluminum
- Installation Ceiling Recessed, spring type
- Dimension 280x110mmx52mm(H)/Cutout 280x100mm
- LED Driver Remote
- Trimless version No

Electronic control gear

NON-DIM/Dimmable

IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.

Light Distribution For 3000K

spot 24°			medium 36°		
h(m)	E(lx)	ø(m)	h(m)	E(lx)	ø(m)
1	7878	ø0.46	1	4358	ø0.64
2	1969	ø0.91	2	1089	ø1.29
3	875.3	ø1.36	3	484.2	ø1.93
4	492.4	ø1.82	4	272.4	ø2.58
5	315.1	ø2.27	5	174.3	ø3.22

The specification is subject to change without notes.