




## SQUARE/SPOT LIGHT/JUMBO/BOX/SINGLE/TILTABLE

**Model: SR-DL3360**



 Cutout: 122x122mm

 5-25mm

### Feature:

- Single head square grilled downlight
- Gimble tilt 25 degree
- Reflector type

### Technical data:

- Light source COB or others
- LED Power (max) 18W (500mA, 36V)
- System Power (ref.) 21W (ref. only depends on the ECG)
- Lumen flux (typ.) 1850lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index  $Ra \geq 90$
- MacAdam Step 3
- Beam Angle 15D, 24D, 36D Reflector
- Tilttable Yes
- Ingress protection IP21
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Construction Aluminum
- Installation Ceiling Recessed, spring type
- Dimension 131x131mmx72mm(H)/Cutout 122x122mm
- LED Driver Remote
- Trimless version No

### Electronic control gear

NON-DIM/Dimmable  MP series

1-10V/0-10V/DALI  SC series

Other brand is available upon request

\*Use IDP multi-power LED Driver can trim down the output power according to actual application.

**\*\*Accessories (optional): Honeycomb, diffuser\*\***

**\*\*The specification is subject to change without note.\*\***