

FLOAT/SPOT DOWNLIGHT/FIXED/MEDIUM/ROUND

Model: RR-DL3028



Feature:

- Compact recessed downlight
- Pendant effect
- Anti-glare

Technical data:

- Light source COB or others
- LED Power (max) 9W (150mA, 36V)
- System Power (ref.) 11W (ref. only depends on the ECG)
- Lumen flux (typ.) 750lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index Ra \geq 90
- MacAdam Step 3
- Beam Angle 15D, 24D, 36D PMMA Lens
- Tiltable No
- Ingress protection IP54
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black/
- Construction Aluminum
- Installation Ceiling Recessed, spring type
- Dimension 70mm(OD)x58mm(H)/Cutout 64mm
- LED Driver Remote
- Trimless version No

Electronic control gear


NON-DIM/Dimmable **IDP** MP series

1-10V/0-10V/DALI **IDP** SC series

Other brand is available upon request

Light Distribution For 2700K
wide 35.7°

h(m)	E(lx)	ø(m)
1	1286	ø0.64
2	321.4	ø1.28
3	142.8	ø1.93
4	80.35	ø2.57
5	51.43	ø3.22



⊙ Cutout: 64mm

⊞ 5-25mm

****The specification is subject to change without notes.****