


FLOAT/SPOT LIGHT/FIXED/SQUARE

Model: RR-DL3027



➔ Cutout: 64mm

▨ 5-25mm

Feature:

- Compact recessed downlight
- Pendant effect
- Anti-glare

Technical data:

- Light source COB or others
- LED Power (max) 9W (250mA, 36V)
- System Power (ref.) 11W (ref. only depends on the ECG)
- Lumen flux (typ.) 600lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index $Ra \geq 90$
- MacAdam Step 3
- Beam Angle 15D, 24D, 36D PMMA Lens
- Tilttable No
- Ingress protection IP54
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Construction Aluminum
- Installation Ceiling Recessed, spring type
- Dimension 70x70mmx50mm(H)/Cutout 64mm
- LED Driver Remote
- Trimless No

Electronic control gear

NON-DIM/Dimmable

IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.

Light Distribution For 2700K wide 35,6°

h(m)	E(lx)	ø(m)
1	1282	ø0.64
2	320.5	ø1.28
3	142.5	ø1.93
4	80.14	ø2.57
5	51.29	ø3.22

****The specification is subject to change without note.****