


## FLOAT/SPOT LIGHT/FIXED/CUBE

**Model: RR-DL3025**



↻ Cutout: 64mm

≡ 5-25mm

### Feature:

- Compact recessed downlight
- Pendant effect
- Anti-glare

### Technical data:

- Light source COB or others
- LED Power (max) 9W (250mA, 36V)
- System Power (ref.) 11W (ref. only depends on the ECG)
- Lumen flux (typ.) 600lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index  $Ra \geq 90$
- MacAdam Step 3
- Beam Angle 15D, 24D, 36D PMMA Lens
- Tilttable No
- Ingress protection IP54
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Construction Aluminum
- Installation Ceiling Recessed, spring type
- Dimension 70x70mmx95mm(H)/Cutout 64mm
- LED Driver Remote
- Trimless version No

### Electronic control gear

NON-DIM/Dimmable

**IDP** MP series

1-10V/0-10V/DALI

**IDP** SC series

Other brand is available upon request

\*Use IDP multi-power LED Driver can trim down the output power according to actual application.

Light Distribution For 2700k  
medium 24.8°

h(m)	E(lx)	ø(m)
1	2022	ø0.44
2	505,6	ø0.88
3	224,7	ø1.32
4	126,4	ø1,76
5	80.90	ø2.20

**\*\*The specification is subject to change without note.\*\***