

SHOWER/SPOT LIGHT/FIXED/IP65

Model: RR-DL3043



Feature:

- Compact recessed downlight
- Interchangeable bezels (optional: square bezels)
- IP65

Technical data:

- Light source COB or others
- LED Power (max) 9W (250mA, 36V)
- System Power (ref.) 11W (ref. only depends on the ECG)
- Lumen flux (typ.) 700lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index Ra \geq 90
- MacAdam Step 3
- Beam Angle 24D, 36D, 45D PMMA Lens
- Tilttable No
- Ingress protection IP65
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black/Chrome/Brushed Nickel/Brushed Brass
- Construction Aluminum
- Installation Ceiling Recessed, spring type
- Dimension 82mm(OD)x51mm(H)/Cutout 70mm
- LED Driver Remote
- Trimless version No

Electronic control gear

NON-DIM/Dimmable


IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.



⊕ Cutout: 70mm

⊕ 5-25mm

Light Distribution For 2700K
medium 35.2°

h(m)	E(lx)	ø(m)
1	2185	ø0.63
2	546.2	ø1.27
3	242.8	ø1.90
4	136.6	ø2.54
5	87.40	ø3.17

**** OPTIONAL: Square Bezels****

****The specification is subject to change without note.****