

MINI CABINET/SPOT DOWNLIGHT/WALL WASHER/FIXED

Model: RR-DL3103



Feature:

- MINI wall washer

Technical data:

- Light source: High Power LED
- LED Power (max): 4.5W (500mA, 9V)
- System Power (ref.): 7 (ref. only depends on the ECG)
- Lumen flux (typ.): 250lm
- Colour temperature: 2700K, 3000K, 4000K
- Colour rendering index: $Ra \geq 90$
- MacAdam Step: 3
- Beam Angle: 15D, 36DPMMA Lens
- Tilttable: No
- Ingress protection: IP21
- Operation temperature: 0-40C
- Protection Class: III
- LED Life time: 50,000h L70B10
- Finishing: White/Black
- Construction: Aluminum
- Installation: Ceiling Recessed, spring type
- Dimension: 60mm(OD)x40mm(H)/Cutout 52mm
- LED Driver: Remote
- Trimless version: No

Electronic control gear

NON-DIM/Dimmable


IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.



↻ Cutout: 52mm

≡ 5-25mm

Light Distribution For 2700K

spot 19°			wide 35°		
h(m)	E(lx)	ø(m)	h(m)	E(lx)	ø(m)
1	1487	ø0.33	1	621.9	ø0.60
2	371.8	ø0.66	2	155.5	ø1.20
3	165.2	ø1.00	3	69.10	ø1.80
4	92.94	ø1.33	4	38.87	ø2.40
5	59.48	ø1.66	5	24.88	ø3.01

****The specification is subject to change without note.****