

MINI CABINET/SPOT LIGHT/KEY HOLE/WALL WASHER/TITLABLE

Model: RR-DL3296



Feature:

- Key hole with wall washer
- Up to 4.5W LED power

Technical data:

- Light source High Power LED
- LED Power (max) 4.5W (500mA, 9V)
- System Power (ref.) 7 (ref. only depends on the ECG)
- Lumen flux (typ.) 250lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index $Ra \geq 90$
- MacAdam Step 3
- Beam Angle 15D, 24D, 36D PMMA Lens
- Tilttable Yes
- Ingress protection IP21
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Construction Aluminum
- Installation Ceiling Recessed, spring type
- Dimension 51mm(OD)x67mm(H)/Cutout 47mm
- LED Driver Remote
- Trimless version No

Electronic control gear

NON-DIM/Dimmable


IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.



↻ Cutout: 47mm

≡ 5-25mm

Light Distribution For 3000K

spot 15°			medium 20°			wide 36°		
h(m)	E(lx)	ø(m)	h(m)	E(lx)	ø(m)	h(m)	E(lx)	ø(m)
1	1972	ø0.27	1	1985	ø0.35	1	835.0	ø0.63
2	492.9	ø0.54	2	496.3	ø0.70	2	208.7	ø1.27
3	219.1	ø0.82	3	220.6	ø1.06	3	92.77	ø1.91
4	123.2	ø1.09	4	124.1	ø1.41	4	52.19	ø2.55
5	78.87	ø1.36	5	79.41	ø1.77	5	33.40	ø3.19

****The specification is subject to change without note.****