

MINI CABINET/SPOT LIGHT/MINI DEEP/FIXED/40mm

Model: RR-DL3325



Feature:

- Deep recessed
- Low UGR

Technical data:

- Light source High Power LED
- LED Power (max) 2.1W (700mA, 3V)
- System Power (ref.) NA (ref. only depends on the ECG)
- Lumen flux (typ.) 150lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index $Ra \geq 90$
- MacAdam Step 3
- Beam Angle 12D, 20D, 36D PMMA Lens
- Tiltable No
- Ingress protection IP21
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Construction Aluminum
- Installation Ceiling Recessed, spring type
- Dimension 40mm(OD)x50mm(H)/Cutout 35mm
- LED Driver
- Trimless version No

Electronic control gear

NON-DIM/Dimmable


IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.



↻ Cutout: 35mm

⚙ 5-25mm

Light Distribution For 3000K
spot 12°

h(m)	E(lx)	ø(m)
1	749.9	ø0.30
2	187.5	ø0.60
3	83.32	ø0.90
4	46.87	ø1.20
5	30.00	ø1.50

****The specification is subject to change without note.****