


## SPOT/CYLINDAR/RECESSED/TILTABLE

**Model: RR-DL3181**



↻ Cutout: 52mm

≡ 5-25mm

### Feature:

- Recessed slim cylinder spot light
- 355 degree rotate and 90 degree tilt
- Interchangeable baffle

### Technical data:

- Light source COB or others
- LED Power (max) 7.2W (200mA, 36V)
- System Power (ref.) 9W (ref. only depends on the ECG)
- Lumen flux (typ.) 650lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index Ra $\geq$ 90
- MacAdam Step 3
- Beam Angle 20D, 40D, 60D Reflector
- Tilttable Yes
- Ingress protection IP21
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Baffle Finishing White/Black/silver grey/sand brass
- Construction Aluminum
- Installation Ceiling Recessed, Spring type
- Dimension 47.5mm(OD)x90mm(H)/Cutout 52mm
- LED Driver Remote
- Trimless version No

### Electronic control gear

NON-DIM/Dimmable

**IDP** MP series

1-10V/0-10V/DALI

**IDP** SC series

Other brand is available upon request

\*Use IDP multi-power LED Driver can trim down the output power according to actual application.

Light Distribution For 3000K  
wide 38°

| h(m) | E(lx) | ø(m)  |
|------|-------|-------|
| 1    | 717.5 | ø0.64 |
| 2    | 179.4 | ø1.28 |
| 3    | 79.72 | ø1.93 |
| 4    | 44.84 | ø2.57 |
| 5    | 28.70 | ø3.21 |

**\*\*The specification is subject to change without note.\*\***