


SPOT/CYLINDAR/SLIM/SURFACE MOUNT

Model: SU-DL3045



Feature:

- Surface Mount cylinder spot light
- 355 degree rotate and 90 degree tilt
- Stylish shape bracket

Technical data:

- Light source AC COB
- LED Power (max) NA
- System Power (ref.) 220Vac, 15W (ref. only depends on the ECG)
- Lumen flux (typ.) 950lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index $Ra \geq 90$
- MacAdam Step 3
- Beam Angle 15D, 38D, 60D Reflector
- Tilttable Yes
- Ingress protection IP21
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Baffle Finishing White/Black/silver grey/sand brass
- Construction Aluminum
- Installation Surface mount
- Dimension 60mm(OD)x175mm(H)
- LED Driver NA
- Trimless version No

Electronic control gear

NO ECG need

Light Distribution For 3000K
wide 36°

h(m)	E(lx)	ø(m)
1	1700	ø0.67
2	425.0	ø1.35
3	188.9	ø2.03
4	106.2	ø2.70
5	68.00	ø3.38

****Build in LED driver version also available****

****The specification is subject to change without note.****