

## TRACK/ DIFFUSED LIGHT/48VDC MAGNET TRACK

**Model: TRA-TR3070**



### Feature:

- Diffused Light, track light
- Low Voltage 48VDC MAGNET track.

### Technical data:

- |                          |                                   |
|--------------------------|-----------------------------------|
| ▪ Light source           | SMD LEDs                          |
| ▪ LED Power (max)        | 25.2W (700mA, 36V)                |
| ▪ System Power (ref.)    | NA (ref. only depends on the ECG) |
| ▪ Lumen flux (typ.)      | 1600lm                            |
| ▪ Colour temperature     | 2700K, 3000K, 4000K               |
| ▪ Colour rendering index | Ra $\geq$ 90                      |
| ▪ MacAdam Step           | 3                                 |
| ▪ Beam Angle             | FLOOD                             |
| ▪ Tilttable              | No                                |
| ▪ Ingress protection     | IP21                              |
| ▪ Operation temperature  | 0-40C                             |
| ▪ Protection Class       | III                               |
| ▪ LED Life time          | 50,000h L70B10                    |
| ▪ Finishing              | White/Black                       |
| ▪ Construction           | Aluminum                          |
| ▪ Installation           | Track DC48V                       |
| ▪ Dimension              | 600x22.3x23.7mm                   |
| ▪ LED Driver             | Build I track LED driver          |
| ▪ Trimless version       | NA                                |

### Electronic control gear

Build in track On/Off LED Driver  
(Dimmable LED Driver is on request)

**\*\*The specification is subject to change without note.\*\***

