

## PENDANTS/TUBULAR/LONG SLIM DESIGN

**Model: SUP-PL3007**



### Feature:

- Spot pendant light 45mm diameter
- Long slim tubular design
- Build in LED Driver

### Technical data:

- Light source COB or others
- LED Power (max) 4.5W (500mA, 9V)
- System Power (ref.) 7W (ref. only depends on the ECG)
- Lumen flux (typ.) 350lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index  $Ra \geq 90$
- MacAdam Step 3
- Beam Angle 15D, 24D, 36D PMMA Lens
- Tilttable No
- Ingress protection IP21
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Construction Aluminum
- Installation Suspension
- Dimension 45mm(OD)x700mm(H)
- LED Driver Build in
- Trimless version NA

### Electronic control gear

Build in On/Off LED Driver  
(Dimmable LED Driver is on request)

#### Light Distribution For 2700K

spot 13°			medium 19°			wide 35°		
h(m)	E(lx)	ø(m)	h(m)	E(lx)	ø(m)	h(m)	E(lx)	ø(m)
1	3033	ø0.22	1	1487	ø0.33	1	621.9	ø0.60
2	758,4	ø0.44	2	371.8	ø0.66	2	155,5	ø1,20
3	337.1	ø0.67	3	165.2	ø1.00	3	69.10	ø1.80
4	189.6	ø0.89	4	92.94	ø1.33	4	38.87	ø2.40
5	121.3	ø1.12	5	59.48	ø1.66	5	24.88	ø3.01

**\*\*The specification is subject to change without note.\*\***