


TRIMLESS/SPOT LIGHT/TILTABLE/RECESSED/DOUBLE REFLECTOR

Model: RR-DL3197



Ⓞ Cutout:85mm

Feature:

- Deep ceiling Recessed
- Trimless design with double reflector
- EXTRA Low glare

Technical data:

- Light source CREE COB or others
- LED Power (max) 12.6W (350mA, 36V)
- System Power (ref.) 15W (ref. only depends on the ECG)
- Lumen flux (typ.) 800lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index Ra \geq 90
- MacAdam Step 3
- Beam Angle 15D, 24D, 36D Reflector type
- Tilttable Yes
- Ingress protection IP21
- Operation temperature 0-40C
- Protection Class III
- LED Lifetime 50,000h L70B10
- Finishing White RAL9003/Black RAL9005
- Baffle Finishing White/Black/Chrome
- Construction Aluminum
- Installation Trimless, Ceiling Recessed
- Dimension 84mm(OD)x120mm(H)/Cutout 85mm
- LED Driver Remote

Electronic control gear

NON-DIM/Dimmable

IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.

LIGHT DISTRIBUTION for 2700K wide 33°

h(m)	E(lx)	Ø(m)
1	2665	Ø0.60
2	666.2	Ø1.20
3	296.1	Ø1.80
4	166.6	Ø2.40
5	106.6	Ø3.00

Photometric 2700K 36D Ra.90

The specification is subject to change without note.