


TRIMLESS/SPOT LIGHT/GIMBLE/RECESSED/SQUARE

Model: SR-DL3163



Feature:

- Step in square trimless spot light
- Low UGR
- Gimble tilt 25 degree

Technical data:

- Light source COB or others
- LED Power (max) 7.2W (200mA, 36V)
- System Power (ref.) 9W (ref. only depends on the ECG)
- Lumen flux (typ.) 600lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index Ra \geq 90
- MacAdam Step 3
- Beam Angle 24D,36D, 45D PMMA Lens
- Tilttable Yes
- Ingress protection IP21
- Operation temperature 0-40C
- Protection Class III
- LED Lifetime 50,000h L70B10
- Finishing White RAL9003/Black RAL9005
- Construction Aluminum
- Installation Trimless, Ceiling Recessed
- Dimension 103x103mm/Cutout 105x105mm
- LED Driver Remote

Electronic control gear

NON-DIM/Dimmable

IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.

Light Distribution For 3000K

medium 36°			wide 44°		
h(m)	E(lx)	ø(m)	h(m)	E(lx)	ø(m)
1	955.6	ø0.81	1	738.7	ø0.83
2	238.9	ø1.62	2	184.7	ø1.67
3	106.2	ø2.43	3	82.08	ø2.51
4	59.73	ø3.24	4	46.17	ø3.34
5	38.23	ø4.06	5	29.55	ø4.17

The specification is subject to change without note.