



TRIMLESS/SPOT LIGHT/GIMBLE/RECESSED/TWIN HEADS

Model: SR-DL3115



Cutout: 201x113mm



Feature:

- TWIN head trimless square grilled downlight
- Low UGR
- Gimble tilt 30 degree

Technical data:

- Light source COB or others
- LED Power (max) 2x7.2W (200mA, 36V)
- System Power (ref.) 2x9W (ref. only depends on the ECG)
- Lumen flux (typ.) 2x600lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index $Ra \geq 90$
- MacAdam Step 3
- Beam Angle 24D, 36D, 45D PMMA Lens
- Tilttable Yes
- Ingress protection IP21
- Operation temperature 0-40C
- Protection Class III
- LED Lifetime 50,000h L70B10
- Finishing White RAL9003/Black RAL9005
- Construction Aluminum
- Installation Trimless, Ceiling Recessed
- Dimension 199x109mm/Cutout 201x103mm
- LED Driver Remote

Electronic control gear

NON-DIM/Dimmable

IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.

Light Distribution For 3000K

medium 31°

h(m)	E(lx)	ø(m)
1	2270	ø0.55
2	567.5	ø1.11
3	252.2	ø1.66
4	141.9	ø2.22
5	90.81	ø2.77

The specification is subject to change without note.